Cumulus® Web Client 8.5

- Overview
- System Requirements
- Product Documentation
- Installation
- Known Issues

Overview

Canto® Cumulus Web Client enables registered users to access Cumulus Servers via Web browsers for secure asset uploads, downloads and complete metadata editing. All Internet-accessible catalogs are “live,” so updates are reflected immediately. Each user connection uses one of the Server’s user licenses. Connected users can access any Cumulus catalogs and cataloged assets to which they have permissions access. Permissions options are based on the Cumulus edition in use – all permissions configured on the Cumulus Server are honored.

For details on all Canto's Digital Asset Management products and services go to: www.canto.com

System Requirements

- Windows 7, Windows Vista™ (and latest patches), Windows XP (SP2 and latest patches), Windows Server™ 2003 (SP1 and latest patches), or Windows Server™ 2008 – all including Microsoft Windows Installer 3.1
- Mac OS X version 10.5/10.6 (latest patches recommended) or
  Mac OS X Server version 10.5/10.6 (latest patches recommended)
- Oracle Solaris 9 (or later) for SPARC processors
- Linux x86 (libc version 6, kernel version 2.6.27.7, libstdc++.so.6)
  Tested on: openSUSE 11.1;
  Not supported: Red Hat Linux 8.x; SuSE Linux 8.x and lower
- Java SE 6 JDK or higher, either 32-bit or 64-bit, depending on the Web Client version you want to install.
- Web application server - supporting Servlet API 2.4 - JSP2.0 or higher (e.g. Apache Jakarta Tomcat 6.0)
- Cumulus Workgroup or Cumulus Enterprise Server 8.5 or later
  with an active Web Client 8.5 serial number.
- Cumulus Java Classes 8.5
- Web Application Server
  supporting Servlet API 2.4 – JSP2.0 - or later
  if Jakarta Tomcat is employed: it has to be at least version 6.0.26

NOTE: For your convenience the Cumulus Web Client installer includes a Web application server (Jakarta Tomcat 6.0.26) and the Cumulus Java Classes 8.5.

Product Documentation

Cumulus Web Client comes with the following manuals in PDF format:

- "Cumulus Web Client – Administrator Guide". This guide describes how how to install and configure Web Client.
- "Cumulus Web Client – Quick Reference User Guide". This guide describes how to use a Cumulus Web Client out-of-the-box installation with a Web browser.

You can download the documentation from the Canto website.

© 2011, Canto GmbH. All Rights Reserved.

Installation

Detailed installation instructions on installing the Cumulus Web Client components can be found in the "Cumulus Web Client – Administrator Guide."

NOTE: Jakarta Tomcat Web application server
Before you configure Web Client, the Tomcat Web application server must have been started once to unpack the WAR file. In addition under Solaris, you have to invoke the URL accessing Web Client. The default URL is http://0.0.0.0:8080/CumulusE. Replace 0.0.0.0 with your Web application server's IP address. 8080 is the default port used by the Web application server).

© 2011, Canto GmbH. All Rights Reserved.